



Rembrandt 2,5/4 kW

The NEW technology in discharge Daylight Fixtures

MOD. 2532



WEIGHT:

- 19 Kg.

CONSTRUCTION:

- Fixture housing in STAINLESS STEEL (INOX).
- BOTTOM SKID on SHOCK ABSORBERS, to increase protection during transportation and stocking.

FINISHING:

- SAND BLASTED AND CHEMICALLY TREATED MATT STAINLESS STEEL (INOX).

PROTECTION FACTOR:

- IP 23, allowing the use of the fixture during moderate rain.

DISCHARGE LAMP TYPES:

- Single ended Hot Re-strike either 2,5 kW or 4 kW discharge lamps

DOUBLE POWER

- QUICK ACTION TOOL FREE lamp holder mechanism to set the fixture for either 2,5 or 4 kW lamp use.

INNOVATIVE PATENT PENDING IGNITER SYSTEM:

- TWO STAGE IGNITER, eliminating the need of HIGH VOLTAGE isolated movable internal cable.
- SILENT operation of the IGNITER also in FLICKER FREE mode.

PHOTOMETRIC DATA REMBRANDT 2.500/4.000 W						
Values measured with: MSR 2500 HR, MSR 4000 HR, 300 mm. Φ Fresnel Lens						
METERS						
TYPICAL DISTANCES		6 m	12 m	18 m	24 m	
LIGHT CENTER VALUES		Candle Power		LUX		
SPOT	2,5 kW	1.711.000	47.528	11.882	5.281	2.970
	4 kW	2.053.000	57.028	14.257	6.336	3.564
FLOOD	2,5 kW	115.350	3.204	801	356	200
	4 kW	171.200	4.756	1.189	528	297
LUX AT ANY DISTANCE = Candle Power : [Distance(in m)]²						
BEAM ANGLE (50% of center value):		BEAM DIAMETER in meters				
SPOT	8,0°	0,8 m	1,7 m	2,5 m	3,4 m	
FLOOD	58,0°	6,7 m	13,3 m	20,0 m	26,6 m	



Patent Pending